NEWLY DEVELOPED SPECIAL FOAM! POWER SOFT

Effective fine finish with both single or double action sander Ideal for removal of paints, burn marks, scratches, weld spots etc.



FEATURES

MARKLESS FINISH

With the high elasticity of newly developed special foamed material, POWER SOFT can contact with damaged surface smoothly and evenly for markless fine featheredge.


NO LOADING

There never happens loading problems due to repeating wasting and reproduction of foam material itself and self-sharpening of abrasive grains by the friction of grinding.


FINER FINISH RESULT

As abrasive grains studded into the elastic foam move up and down structurally, POWER SOFT can contact evenly with the work surface for finer finish result

INNOVATIVE MECHANISM OF POWER SOFT



Abrasive grains equally studded into special foam material



When starting rotation, both abrasive grains and special foam contact with the work surface in the same time.



Elasticity of the special foam carries out the self-sharpening of abrasive grains for continuous grinding performance.




Special foam material also repeats selfreproduction by itself to prevent the loading problem.

<COMPARATIVE EXAMPLE>

Considerable reduction of working time!

POWER SOFT can reduce work time and processes for metal sheet such as a smoothing out of scratches etc. which needed about 5 steps of operation by conventional tools and process.



	TYPE			PowerSoft-100	PowerSoft-60	PowerSoft-25
SIZE				DIA.100mm x 16mm(I.D.)	DIA.60mm x M6 SCREW	DIA.25mm x M6 SCREW
MAX RPM				12,000 rpm	15,000 rpm	20,000rpm
PACKAGES				5	5	10
GRIT SIZE	COASE	C1 (Gray)	#60<fiber</td><td colspan=3>APPLICATIONS</td></tr><tr><td>C3 (Gray)</td><td>#60</td><td>REMOVAL OF PAINT</td><td>< By Order></td></tr><tr><td>C8 (White)</td><td>#80</td><td>GRINDING OF BREAK D</td><td>< By Order></td></tr><tr><td>MIDDLE</td><td>M3 (White)</td><td>#320</td><td>< By Order></td><td>REMOVAL OF BURN MARKS, FINISH GRINDING ETC.</td><td>< By Order></td></tr><tr><td rowspan=2>FINE</td><td>F6 (White)</td><td>#600</td><td>< By Order></td><td>REMOVAL OF RUST, STAIN, BURN MARK OF DRESSED STAINLESS OR PLATING</td><td rowspan=2>REMOVAL OF SCRATCHES, DUSTS ETC. REMOVAL OF WELD SPOT, BURN MARKS</td></tr><tr><td>F10 (White)</td><td>#1000</td><td>< By Order></td><td>< By Order></td></tr><tr><td colspan=4>ETC.</td><td>SPACER ATTACHED</td><td>AVAILABLE ON COLLET CHUCK DIA. 6mm STRAIGHT SHAFT</td><td>AVAILABLE ON COLLET CHUCK DIA. 6mm STRAIGHT SHAFT</td></tr></tbody></table>			